

**STBOS** min.10 cm max.70 cm B\* ≤ 90

**STBOP** min.6 cm B\* ≤ 60

**STBOPV** min.13 cm B\* ≤ 60 I\* = A\* - 5,8 cm

# Trim Bath

**[A]** attacco standard  
standard connection  
raccord standard  
standard Anschluss  
conexión estándar

**[B]** attacco speciale  
special connection  
raccord spéciale  
speziell Anschluss  
conexión especial

**[B50]** attacco interasse 5 cm  
pipe centres 5 cm  
raccords 5 cm  
5 cm Achsabstand Anschluss  
conexión entre ejes: 5 cm.

A* cm	inches	B* cm	inches	I* cm	inches	art*	ON STOCK	L*	BTU Δt 50°	watt Δt 50°	E* M* ET* MT*
80.0	31.5	40.0	15.7	36.0	14.2	HB15000S080040B	ON STOCK	5.1	1 520	446	350
80.0	31.5	50.0	19.7	46.0	18.1	HB15000S080050B	ON STOCK	6.0	1 896	556	500
80.0	31.5	60.0	23.6	56.0	22.0	HB15000S080060B	ON STOCK	6.9	2 267	665	500
116.0	45.7	40.0	15.7	36.0	14.2	HB15000S116040B	ON STOCK	7.3	2 120	622	500
116.0	45.7	50.0	19.7	46.0	18.1	HB15000S116050B	ON STOCK	8.5	2 639	774	700
116.0	45.7	60.0	23.6	56.0	22.0	HB15000S116060B	ON STOCK	9.8	3 156	925	700
152.0	59.8	40.0	15.7	36.0	14.2	HB15000S152040B	ON STOCK	9.4	2 703	793	700
152.0	59.8	50.0	19.7	46.0	18.1	HB15000S152050B	ON STOCK	11.0	3 364	986	700
152.0	59.8	60.0	23.6	56.0	22.0	HB15000S152060B	ON STOCK	12.6	4 023	1 180	1000
188.0	74.0	40.0	15.7	36.0	14.2	HB15000S188040B	ON STOCK	11.5	3 348	982	700
188.0	74.0	50.0	19.7	46.0	18.1	HB15000S188050B	ON STOCK	13.5	4 079	1 196	1000
188.0	74.0	60.0	23.6	56.0	22.0	HB15000S188060B	ON STOCK	15.5	4 879	1 431	1000

art*	watt	E*	M*	ET*	MT*
SOVRES0350_2	350				
SOVRES0500_2	500				
SOVRES0700_2	700				
SOVRES1000_2	1000				
KITRES0350_2	350				
KITRES0500_2	500				
KITRES0700_2	700				
KITRES1000_2	1000				

A\* = altezza / height / hauteur / Höhe / alto    B\* = larghezza / width / longueur / Breite / ancho    art\* = articolo / model / modèle / Artikel / artículo  
 I\* = interasse / pipe centres / distance entre depart et retour / Achsabstand / distancia entre las conexiones    P\* = pagina / page / page / Seite / página  
 E\* = elettrico / electrical / électrique / elektrische / eléctrico    M\* = misto / dual application / mixte / der gemischter Ausführung / kit mixto  
 ET\* = elettrico termostato ambiente / thermostat / thermostat / der Thermostat / termostato  
 MT\* = misto termostato ambiente / dual application with thermostat / mixte avec thermostat / der gemischter Ausführung mit Thermostat / kit mixto con termostato  
 L\* = contenuto acqua / content / volume / Inhalt / volumen

Kcal = Watt x 0.860  
BTU = Watt x 3.413

Watt Δt 60° = Watt Δt 50° x 1.255  
Watt Δt 40° = Watt Δt 50° x 0.758  
Watt Δt 30° = Watt Δt 50° x 0.530  
Watt Δt 20° = Watt Δt 50° x 0.320

p max = 10.0 bar

Colori/ colours / couleurs / Farbe / colores

[ BIAN ] B standard  
T + 10%  
S + 20%

[ RAL ] RAL non inclusi in tabella  
special Ral colours  
couleurs Ral spéciales  
RAL Farbe nicht in der Tabelle inbegriffen  
colores RAL especiales

Ulteriori dettagli  
Further details  
Ulérieures détails  
Weitere Einzelheiten  
Otros detalles

P\* 120